

5120 Pigmented Polyaspartic Flooring

Ultra Fast Drying Tough Color Coat

5120 Polyaspartic Extra Fast Drying Pigmented Concrete Flooring Topcoat

Our 5120 Polyaspartic has been formulated to be one of the easiest Polyaspartic's Floor Coatings to apply by roller and brush, making it the ideal topcoat to use over a variety of Concrete and Epoxy Flooring. This unique formulation allows for more than 45 minutes of potlife (which is more than enough for most Floor Coating installers), yet the material dries in as little as 20 minutes when applied to the flooring surface. In most cases you can get back on the floor in 60 minutes and it will accept light vehicle traffic the next day (please use care since it is not fully cure). Use 5120 when you need a faster turnaround time and you can install it at temperatures ranging from 30-100 Degrees Fahrenheit

Easily Applied over Epoxy Floors

We have reduced the 5120 Polyaspartic viscosity down to levels comparable to a medium solids CRU (chemical resistant urethane). The benefits of this is that the Polyaspartic Floor Sealer is easier to install, has more pot life, cures to a hard film faster (dries in just about an hour) and is suitable for exterior exposure without yellowing. The only drawback is that 5120 Flooring Polyaspartic is considered combustible and its use should be restricted to well ventilated areas.

Fast Turn Around Time

Use 5120 Polyaspartic Pigmented Floor Sealer when you need a faster turnaround time so you can get that coated concrete floor back in service fast. 5120 is perfect when you want a solid color topcoat over your epoxy floor. 5120 is abrasion resistant and UV resistant plus it dries really fast (dries in under 60 minutes) so you can get your floor back in service quickly.

Features and Advantages:

- ☑ Below 50 VOC
- ☑ High gloss
- ☑ 63% solids
- ☑ Medium Build
- ☑ Foot traffic in as little as 2 hours
- ☑ Pneumatic wheel traffic in as little as 24 hours
- ☑ Dries quick
- ☑ Non-yellowing
- ☑ Good Resistance to most chemicals
- ☑ Abrasion Resistant
- ☑ 5120 is Skydrol Resistant
- ☑ Will cure at temperatures just above freezing
- ☑ Extremely Fast Drying



Ideally suited as a solid color floor coating where fast return to service is paramount

Suitable over:

- ✓ Garage Floors
- ✓ Retail Floors
- ✓ Industrial Floors
- ✓ Any Concrete Floor
- ✓ Most Previously Coated Floors – consult with manufacturer


LIMITATIONS

- 5120 is combustible and proper ventilation should be used during its application
- Requires moisture/vapor barrier for surfaces with a MVT of 3lbs or higher
- Will not bridge cracking
- Not resistant to strong acids.
- Do not use over Acrylic Sealers or Acrylic Primers unless they are de-glossed first
- Topcoats must be applied over it while tacky or screening/sanding of the 5120 will be required in order to get proper tooth for the topcoat to bond to

5120 Colors Available



Whisper Grey



Slate Grey



Cottonwood



1-800-535-3325
Tel: 714-829-2600
sales@deckcoatings.com
www.deckcoatings.com
245 Carl Karcher Way
Anaheim, CA 92801 U.S.A.
©2015 by Versatile Building Products