SAFETY DATA SHEET

5400 Gloss Waterbase Chemical Resistant Urethane Clear Flooring Topcoat A-Component



GHS product identifier	: 5400 Gloss Waterbase Chemical Resistant Urethane Clear Flooring Topcoat A- Component
Product code	: Not available.
Other means of identification	: Not available.
Product type	: Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Waterborne Polyurethane Concrete Floor Coating Polyol.

Supplier's details	:	Versatile Building Products 245 W. Carl Karcher Way Anaheim, CA 92801 Tel.: (714) 829-2600 Toll Free: (800) 535-3325 Email: contactus@versatile.net Website: www.versatile.net	
Emergency telephone	:	InfoTrac: 1-800-535-5053	

number (with hours of operation) (8:00 a.m. – 5:00 p.m. PST)

Section 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the	: SKIN SENSITIZATION - Category 1
substance or mixture	AQUATIC HAZARD (ACUTE) - Category 3 AQUATIC HAZARD (LONG-TERM) - Category 3
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	 H317 - May cause an allergic skin reaction. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements	
Prevention	 P280 - Wear protective gloves. P273 - Avoid release to the environment. P261 - Avoid breathing vapor. P272 - Contaminated work clothing must not be allowed out of the workplace.

Tel:+1-888-GHS-7769 (447-7769) / +1-450-GHS-7767 (447-7767) www.kmkregservices.com www.askdrluc.com www.ghssmart.com





Section 2. Hazards identification

Response	 P363 - Wash contaminated clothing before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of water. P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.
Storage	: Not applicable.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

Ingredient name	%	CAS number
2-(2-Butoxyethoxy)ethanol	≥5 - ≤7	112-34-5
Triethanolamine	≥1 - ≤2.9	102-71-6
bis(1,2,2,6,6-Pentamethyl-4-piperidyl) sebacate	≥0.3 - ≤1	41556-26-7
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	≤0.3	82919-37-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necess	ary first aid measures
Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 20 minutes. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	: Wash with plenty of soap and water. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 20 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately.



Section 4. First aid measures

Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health e	ffects
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sy	<u>imptoms</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No known significant effects or critical hazards.
Indication of immediate I	nedical attention and special treatment needed, if necessary
Notes to physician	In case of inhalation of decomposition products in a fire, symptoms may be delayed

Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides
Special protective actions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.





Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
Methods and materials for co	ont	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or

diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling	
Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store between the following temperatures: 15 to 35°C (59 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.



Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
2-(2-Butoxyethoxy)ethanol	ACGIH TLV (United States, 3/2020).
	TWA: 10 ppm 8 hours. Form: Inhalable
	fraction and vapor
Triethanolamine	ACGIH TLV (United States, 3/2020).
	TWA: 5 mg/m ³ 8 hours.
bis(1,2,2,6,6-Pentamethyl-4-piperidyl) sebacate	None.
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	None.

Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.
Individual protection meas	<u>ures</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.



Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

<u>Appearance</u>	
Physical state	: Liquid. [Opaque.]
Color	: Milky white.
Odor	: Mild.
Odor threshold	: Not available.
рН	: Not available.
Melting point/freezing point	: Not available.
Boiling point, initial boiling point, and boiling range	: >35°C (>95°F)
Flash point	: Closed cup: >93.3°C (>199.9°F)
Evaporation rate	: Not available.
Flammability	: Not available.
Lower and upper explosion limit/flammability limit	: Not available.

ŝ,

Vapor pressure

	Vapo	Vapor Pressure at 20°C			or press	ure at 50°C
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
Chloromethane	3671.9	489.5	OECD 104			
Ethylene oxide	1314.11	175.2				
Acetaldehyde	900.07	120				
Propylene oxide	538	71.7	OECD 104			
Methanol	126.96	16.9				
1,4-Dioxane	30.75	4.1				
Water	23.8	3.2				
Toluene	23.17	3.1				
2-Methoxy- 1-methylethyl acetate	2.7	0.36	OECD 104			
3-Butoxypropan-2-ol	1.05	0.14	OECD 104			
Formaldehyde	1	0.13				
2-Butoxyethanol	0.75	0.1				
2-(2-Butoxyethoxy) ethanol	0.02	0.0027				
2-[2-(2-Butoxyethoxy) ethoxy]ethanol	0.01	0.0013				
Triethanolamine	<0.01	<0.0013				
Propane-1,2-diol, propoxylated	0	0	OECD 104			
Dibutyltin dilaurate	0	0	OECD 104			

Relative vapor density Relative density : Not available.

: 1.047



Solubility in water

Section 9. Physical and chemical properties and safety characteristics

So	lubi	litv
00		

: Not available.

- : Not available.
- : Not applicable.

octanol/water	•
Auto-ignition	temperature

Partition coefficient: n-

Auto-ignition temperature :	Ingredient name	°C	°F	Method	
	Acetaldehyde	175	347		
	1,4-Dioxane	180	356		
	2-[2-(2-Butoxyethoxy)ethoxy]ethanol	202	395.6	DIN 51794	
	(2-Methoxymethylethoxy)propanol	207	404.6		
	2-(2-Butoxyethoxy)ethanol	210	410	DIN 51794	
	2-Butoxyethanol	230	446	DIN 51794	
	3-Butoxypropan-2-ol	260	500	EU A.15	
	Propane-1,2-diol, propoxylated	305	581	EU A.15	
	Triethanolamine	324	615.2		
	2-Methoxy-1-methylethyl acetate	333	631.4	DIN 51794	
	Dibutyltin dilaurate	400	752	EU A.15	
	Ethylene oxide	429	804.2		
	Formaldehyde	430	806		
	Propylene oxide	449	840.2	EU A.15	
	Methanol	455	851		
	Toluene	480	896		
	Chloromethane	632	1169.6		
Decomposition temperature :	Not available.				
Viscosity :	Dynamic: 50 to 150 mPa⋅s (50 to 150 cP)				
Flow time (ISO 2431) :	Not available.				
Particle characteristics					
Median particle size :	Not applicable.				

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid high temperatures.
Incompatible materials	: Reactive or incompatible with the following materials: reactive metals, organic acids and strong oxidizers.



Section 10. Stability and reactivity

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-(2-Butoxyethoxy)ethanol	LD50 Dermal	Rabbit	2700 mg/kg	-
	LD50 Oral	Rat	4500 mg/kg	-
Triethanolamine	LD50 Oral	Rat	7.39 g/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-(2-Butoxyethoxy)ethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 20 mg	-
Triethanolamine	Eyes - Severe irritant Eyes - Mild irritant Skin - Mild irritant	Rabbit Rabbit Rabbit	- - -	20 mg 10 mg 24 hours 560 mg	- - -

Sensitization

There is no data available.

Mutagenicity

There is no data available.

Carcinogenicity

Classification

Product/ingredient name	OSHA	IARC	NTP
Triethanolamine	-	3	-

Reproductive toxicity

There is no data available.

Teratogenicity

There is no data available.

Specific target organ toxicity (single exposure)

There is no data available.

Specific target organ toxicity (repeated exposure)

There is no data available.

Aspiration hazard

There is no data available.

Information on the likely routes of exposure	:	Routes of entry anticipated: Oral, Dermal.
Potential acute health effects		
Eye contact	:	No known significant effects or critical hazards.

- Inhalation
- : No known significant effects or critical hazards.





Section 11. Toxicological information

Skin contact	
Ingestion	

- : May cause an allergic skin reaction.
- : No known significant effects or critical hazards.

Symptoms related to the ph	vsical, chemical and toxicological characteristics
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No known significant effects or critical hazards.
Delayed and immediate effe	ects and also chronic effects from short and long term exposure
<u>Short term exposure</u>	
Potential immediate effects	: No known significant effects or critical hazards.
Potential delayed effects	: No known significant effects or critical hazards.
Long term exposure	
Potential immediate effects	: No known significant effects or critical hazards.
Potential delayed effects	: No known significant effects or critical hazards.
Potential chronic health eff	ects
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)		(vapors)	Inhalation (dusts and mists) (mg/ I)
2-(2-Butoxyethoxy)ethanol	4500	2700	N/A	N/A	N/A
Triethanolamine	7390	N/A	N/A	N/A	N/A





Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
2-(2-Butoxyethoxy)ethanol Triethanolamine	Acute LC50 1300000 μg/L Fresh water Acute EC50 609.98 mg/L Fresh water	Fish - Lepomis macrochirus Crustaceans - Ceriodaphnia dubia - Neonate	96 hours 48 hours
	Acute LC50 11800000 μg/L Fresh water Chronic NOEC 16000 μg/L Fresh water	Fish - Pimephales promelas Daphnia - Daphnia magna	96 hours 21 days

Persistence and degradability

There is no data available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-(2-Butoxyethoxy)ethanol	1	-	low
Triethanolamine	-1	<3.9	low

Mobility in soil

Soil/water partition : Not available. coefficient (Koc)

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-





Section 14. Transport information

Environmental	No.	No.	No.
hazards			

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments

Section 15. Regulatory information

U.S. Federal regulations	: TSCA 8(a) PAIR: (2-Methoxymethylethoxy)propanol; 2-Methoxy-1-methylethyl acetate; Acetaldehyde
	TSCA 8(a) CDR Exempt/Partial exemption: Not determined
	Commerce control list precursor: Triethanolamine
	Clean Water Act (CWA) 307: Chloromethane; Toluene
	Clean Water Act (CWA) 311: Propylene oxide; Acetaldehyde; Formaldehyde; Toluene
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	: Listed
Clean Air Act Section 602 Class I Substances	: Not listed
Clean Air Act Section 602 Class II Substances	: Not listed
DEA List I Chemicals (Precursor Chemicals)	: Not listed
DEA List II Chemicals (Essential Chemicals)	: Not listed
SARA 302/304	

Composition/information on ingredients

			SARA 30	2 TPQ	SARA 3	04 RQ
Name	%	EHS	(lbs)	(gallons)	(lbs)	(gallons)
Propylene oxide	≤0.00001	Yes.	10000	1444.3	100	14.4
Formaldehyde	≤0.00001	Yes.	500	73.9	100	14.8
Ethylene oxide	≤0.00001	Yes.	1000	-	10	-

SARA 304 RQ

: 2415458937.2 lbs / 1096618357.5 kg [276691424.8 gal / 1047390981.4 L]

SARA 311/312 Classification

: SKIN SENSITIZATION - Category 1

Composition/information on ingredients





Section 15. Regulatory information

Name	%	Classification
2-(2-Butoxyethoxy)ethanol	≥5 - ≤7	FLAMMABLE LIQUIDS - Category 4 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
Triethanolamine	≥1 - ≤2.9	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2B
bis(1,2,2,6,6-Pentamethyl- 4-piperidyl) sebacate	≥0.3 - ≤1	SKIN SENSITIZATION - Category 1
Methyl 1,2,2,6,6-pentamethyl- 4-piperidyl sebacate	≤0.3	SKIN SENSITIZATION - Category 1

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	2-(2-Butoxyethoxy)ethanol	112-34-5	≥5 - ≤7
Supplier notification	2-(2-Butoxyethoxy)ethanol	112-34-5	≥5 - ≤7

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts	:	The following components are listed: Triethanolamine

- New York
- New Jersey

Pennsylvania

- : None of the components are listed.
- : The following components are listed: 2-(2-Butoxyethoxy)ethanol; Triethanolamine
- : The following components are listed: Triethanolamine

California Prop. 65

▲ WARNING: This product can expose you to chemicals including Ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including Propylene oxide, Acetaldehyde, Formaldehyde and 1,4-Dioxane, which are known to the State of California to cause cancer, and Methanol, Methyl chloride and Toluene, which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Propylene oxide	-	-
Acetaldehyde	Yes.	-
Formaldehyde	Yes.	-
Ethylene oxide	Yes.	Yes.
1,4-Dioxane	Yes.	-
Methanol	-	Yes.
Methyl chloride	-	-
Toluene	-	Yes.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Ingredient name	List name	Status
Triethanolamine	Schedule III	Listed

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants



Section 15. Regulatory information

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC) Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

United States (TSCA 8b) : All components are active or exempted.

Section 16. Other information

Procedure used to derive the classification

Classification	Justification
SKIN SENSITIZATION - Category 1	Calculation method
AQUATIC HAZARD (ACUTE) - Category 3	Calculation method
AQUATIC HAZARD (LONG-TERM) - Category 3	Calculation method

<u>History</u>	
Date of issue/Date of revision	: 06/30/2021
Date of previous issue	: Not applicable
Version	: 1
Prepared by	: KMK Regulatory Services Inc.
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

