

Issue Date: 03/31/15

Version: 1.3

Revision Date: 05/06/15

Trade Name: Slate Grey Deck Paint

1 Identification

1.1 Product Identifier
Product Name: Slate Grey Deck Paint

1.2 Application of the substance / the preparation:

Waterproofing Sealer

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

 Versatile Building Products
 245 Carl Karcher Way
 Anaheim, Ca 92801
 U.S.A.

Information department

 Health and Safety (8 AM to 5 PM-PST) 1-714-829-2600
 MSDS@garagecoatings.com

1.4 Emergency telephone number:

 Infotrac: (800) 535-5053 (North America)
 (352) 323-3500 (International)

2 Hazard(s) identification

2.1 Classification of the substance or mixture
GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Skin Sensitization	Category 1
Eye irritation	Category 2

2.2 GHS Label Elements, including precautionary statements

Pictogram
Signal Word

Warning

Appearance: Opaque Viscous Liquid **Physical State:** Liquid

Odor: Slight

Hazard statements

 May cause an allergic skin reaction
 Causes serious eye irritation.

Precautionary statement(s) - Prevention

 Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Keep container tightly closed.

Issue Date: 03/31/15

Version: 1.3

Revision Date: 05/06/15

Trade Name: Slate Grey Deck Paint

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
 Wash skin thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Contaminated work clothing should not be allowed out of the workplace.
 Avoid release to the environment.
 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Precautionary statement(s) - Response

IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Call a POISON CENTER or doctor/ physician if you feel unwell.
 If skin irritation or rash occurs: Get medical advice/ attention.
 If eye irritation persists: Get medical advice/ attention.
 Take off contaminated clothing and wash before reuse.
 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
 Collect spillage.

Precautionary statement(s) - Storage

Store in a well-ventilated place. Keep container tightly closed.
 Store in a well-ventilated place. Keep cool.

Precautionary statement(s) - Disposal

Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS – None

3 Composition/information on ingredients

3.1 Mixtures

Chemical Name	CAS #	Wt %
Ammonium hydroxide	1336-21-6	0.1-0.5
Methyl Methacrylate	80-62-6	0.01-0.2
Acrylic copolymer	25035-69-2	35-50
2,2,4-Trimethyl 1-1,3-Pentanediolmonoisobutyrate	25265-77-4	2-8
Ethylene Glycol Monobutyl Ether	111-76-2	<0.5

4 First-aid measures

4.1 Description of first aid measures
--

General advice

Issue Date: 03/31/15

Version: 1.3

Revision Date: 05/06/15

Trade Name: Slate Grey Deck Paint

Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.

After inhalation:

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

After skin contact:

Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

After eye contact:

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Continue rinsing eyes during transport to hospital.

After swallowing:

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms/effects, acute and delayed:

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of immediate medical attention and special treatment needed**5 Firefighting Measures****5.1 Extinguishing media****Suitable extinguishing media**

For small (incipient) fires, use media such as "alcohol" foam, dry chemical, or carbon dioxide. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water.

5.2 Special hazards arising from the substance or mixture

Carbon oxides, Hydrogen chloride gas, Hydrogen fluoride

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

6 Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Issue Date: 03/31/15

Version: 1.3

Revision Date: 05/06/15

Trade Name: Slate Grey Deck Paint

Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

7 Handling and storage

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Store in cool place. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8 Exposure controls/personal protection
--

8.1 Control parameters**Components with workplace control parameters**

Contains no substances with occupational exposure limit values.

8.2 Exposure controls**Appropriate engineering controls**

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment**Eye/face protection**

Tightly fitting safety goggles. Faceshield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Issue Date: 03/31/15

Version: 1.3

Revision Date: 05/06/15

Trade Name: Slate Grey Deck Paint

Body Protection

Impervious clothing, Flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls.

If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

9 Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

a) Appearance	Form: Opaque, viscous liquid Colour: Grey
b) Odour	Slight
c) Odour Threshold	No data available
d) pH	8.5-9.5
e) Melting point/freezing point	0 °C, (32 °F)
f) Initial boiling point and boiling range	No data available
g) Flash point	No data available
h) Evaporation rate	no data available
i) Flammability (solid/gas)	no data available
j) Upper/lower flammability or explosive limits	no data available
k) Vapour pressure	~18 mm Hg (20 °C)
l) Vapour density	No data available
m) Relative density	1.185 g/cm ³ at 25°C (77°F)
n) Water solubility	Soluble
o) Partition coefficient: n-octanol/water	no data available
p) Auto-ignition temperature	no data available
q) Decomposition temperature	no data available
r) Viscosity	200-400 CPS at 25°C (77°F)
s) Explosive properties	no data available
t) Oxidizing properties	no data available

9.2 Other safety information

No data available

10 Stability and reactivity

10.1 Control parameters

Issue Date: 03/31/15

Version: 1.3

Revision Date: 05/06/15

Trade Name: Slate Grey Deck Paint

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Strong bases, Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides, Tin/tin oxides

Other decomposition products - no data available

In the event of fire: see section 5

11 Toxicological Information

11.1 Information on likely routes of exposure**Product information**

Inhalation	Harmful if inhaled
Eye Contact	Avoid contact with eyes
Skin Contact	Harmful if absorbed through the skin
Ingestion	Harmful if swallowed

Component Information**11.2 Information on physical, chemical and toxicological effects**

Symptoms Causes eye irritation. Causes skin irritation. Stomach ache, nausea, vomiting, dullness, vision disorder, and blindness.

11.3 Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization	No data available
Germ cell mutagenicity	No data available
Carcinogenicity	Carcinogenic potential is unknown
Reproductive toxicity	This product does contain known or suspected reproductive hazards
STOT – Single exposure	No data available
STOT – Repeated exposure	No data available

11.4 Numerical measures of toxicity - Product

Not determined

Additional Information

Issue Date: 03/31/15

Version: 1.3

Revision Date: 05/06/15

Trade Name: Slate Grey Deck Paint

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

12 Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Very toxic to aquatic life with long lasting effects.

13 Disposal considerations

13.1 Waste treatment methods**Product**

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14 Transport information

DOT (US)

Not regulated

IMDG

Not regulated

IATA

Not regulated

Issue Date: 03/31/15

Version: 1.3

Revision Date: 05/06/15

Trade Name: Slate Grey Deck Paint

15 Regulatory information**United States Regulatory Information****TSCA 8 (b) Inventory Status**

All Components are listed or exempt from listing on the Toxic Substances Control Act Inventory.

TSCA 12 (b) Export Notification

None above reporting de minimus

SARA 302 Components

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Acute health hazard	Yes
Chronic health hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive hazard	No

California Prop. 65 ComponentsThis product may contain chemical(s) known to the state of California to cause cancer and/or birth defects. For additional information please contact Versatile Building Products Customer Service or msds@garagecoatings.com**Canada Regulatory Information****CEPA DSL/NDSL Status:**

All components are listed on or are exempt from listing on the Domestic Substances List.

16 Other information

Issue Date: 31-Mar-2015

Revision Date: 06-May-2015

Revision Note: Update information



Issue Date: 03/31/15

Version: 1.3

Revision Date: 05/06/15

Trade Name: Slate Grey Deck Paint

HMIS Rating

Health Hazard: 1
Flammability: 0
Physical Hazard: 0

NFPA Rating

Health Hazard: 1
Fire Hazard: 0
Reactivity Hazard: 0

Disclaimer:

THIS MATERIAL SAFETY DATA SHEET (SDS) WAS PREPARED IN ACCORDANCE WITH 29 CFR 1910.1200 BY VERSATILE BUILDING PRODUCTS. VERSATILE BUILDING PRODUCTS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF PRODUCT USE BY OTHERS. THE INFORMATION, RECOMMENDATIONS, AND SUGGESTIONS PRESENTED IN THIS SDS ARE BASED UPON TEST RESULTS AND DATA BELIEVED TO BE RELIABLE. THE END USER OF THE PRODUCT HAS THE RESPONSIBILITY FOR EVALUATING THE ADEQUACY OF THE DATA UNDER THE CONDITIONS OF USE, DETERMINING THE SAFETY, TOXICITY AND SUITABILITY OF THE PRODUCT UNDER THESE CONDITIONS, AND OBTAINING ADDITIONAL OR CLARIFYING INFORMATION WHERE UNCERTAINTY EXISTS. NO GUARANTEE EXPRESSED OR IMPLIED IS MADE AS TO THE EFFECTS OF SUCH USE, THE RESULTS TO BE OBTAINED, OR THE SAFETY AND TOXICITY OF THE PRODUCT IN ANY SPECIFIC APPLICATION. FURTHERMORE, THE INFORMATION HEREIN IS NOT REPRESENTED AS ABSOLUTELY COMPLETE, SINCE IT IS NOT PRACTICABLE TO PROVIDE ALL THE SCIENTIFIC AND STUDY INFORMATION IN THE FORMAT OF THIS DOCUMENT, PLUS ADDITIONAL INFORMATION MAY BE NECESSARY UNDER EXCEPTIONAL CONDITIONS OF USE, OR BECAUSE OF APPLICABLE LAWS OR GOVERNMENT REGULATIONS.