

4010 Pigmented Waterborne Epoxy Sealer

\$44.95 Gal

4010 Epoxy Color Seal System utilizes a 2-component waterborne epoxy technology that is easy to apply, MVE tolerant, ultra-low odor and VOC compliant. 4010 is so easy to apply that even the “Do It Yourselfer” can apply it. 4010 provides an excellent two component option for sealing your interior concrete floor to prevent foreign materials, spills, etc. from being absorbed by the underlying concrete surface.

Waterborne Epoxy Technology

4010 Waterborne Epoxy technology makes it capable of adhering to, and withstanding the effects of moisture vapor emissions from concrete floor slabs. All materials and tools can be cleaned up with water.

Looks Great Too!!

The 4010 provides the look and performance of a 100% Solids Epoxy yet it is much easier to work with due to its waterbased formula. 4010 Concrete Floor Epoxy also develops very high gloss, due to the strong polymer film developed as the system cross-links.

Features and Advantages:

- ☑ MVE Tolerant
- ☑ Great Hide
- ☑ Excellent Sealer Properties
- ☑ Use Over New or Old Concrete
- ☑ Low Odor
- ☑ Easy to Apply
- ☑ Water Clean Up



Apply using a brush and roller



4010 Waterbased Epoxy applied to a garage floor without a clear topcoat



Economical 1 or 2 coat epoxy system for light industrial floors

Solids (vol.):	~63%
Solids (wt.):	~53%
VOC:	49 g/l
Pot-Life:	60 Minutes @75 degrees
Pencil Hardness:	H-2H
Flexibility:	Passes 3/16" Mandrel
Impact Resistance:	
120in./lbs. Direct	
60in./lbs. Reverse	
Abrasion Resistance (CS-17 Disk 1KG):	
62 mg loss	
Chemical Resistance ASTM 1308:	
Gasoline	No Effect
Motor Oil	No Effect
Coffee	No Effect
Windex	No Effect
Formula 409	No Effect
Ethanol	No Effect



245 Carl Karcher Way, Anaheim CA 92801
714-829-2600 www.garagecoatings.com