

4195 Direct to Concrete Epoxy

4195 Direct to Concrete Epoxy

4195 is a Pigmented direct to concrete two part epoxy designed specifically for receiving the vinyl chips. 4195 uses 4150 Vapor Stop as the backbone. The ideal chipping window for 4195 is between 15 and 45 minutes of application, where Vapor Stop's ideal chipping window is 30-60 minutes. 4195 Direct to Concrete Epoxy is available in over 8 colors that are designed to work well with any flake combination. 4195 is self priming which allows the applicator to broadcast into the first coat under most circumstances. 4195 actually wicks into the concrete and bonds so well that you can expect to get over 8lbs of MVE blocking power. 4195 can be accelerated to dry in as little as two hours making a 4-6 hour 1 day installation possible. Best of all the 4195 will still provide at least 8 lbs of MVE protection even when accelerated to dry in two hours. VBP can provide a "Lifetime Adhesion Warranty" to celebrate 10 years with millions of sq ft of failure free installations.

Features and Advantages:

- ☑ Withstands up to 8 lbs of Moisture Vapor Emissions
- ☑ Available in 9 colors
- ☑ Self-Priming Material Allows for a Direct Bond
- ☑ Can be accelerated to dry in 2 hours
- ☑ Lifetime adhesion warranty



Cottonwood



Sandstone



Baja Beige



Whisper Grey



Charcoal



Mocha



White



Black



Beige

versatile



building products

Tel:
714-829-2600
orders@garagecoatings.com
www.garagecoatings.com
245 Carl Karcher Way
Anaheim, CA 92801 U.S.A.
©2002 by Versatile Building Products Rev 03/13